



PCE data sheet

| | |
|---------------------|---|
| article# | 885-6gv |
| article description | CEE-flush socket outlet incl. flush socket Design 16A 5p 6h IP44 (grey) |
| description long | CEE-flush socket outlet incl. flush socket Design 16A 5p 6h IP44 (grey) housing material: PC/ABS rated current: 16A number of poles: 5 (3P+N+PE) clock-position: 6h rated voltage/frequency: 200/346V~ - 240/415V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals color: grey (similar to RAL 7035) flush mounting (incl. Flush socket) hinged lid with inscription field (optional: key lock) IP protection class: IP44 |
| GTIN (EAN) | 9003399665936 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.335 kg |
| packaging quantity | 6 |

| | |
|-------------------------|----------------------------------|
| ETIM 7.0 | EC001318 |
| Current supply | CEE 16 A |
| Number of poles | 5 |
| Voltage acc. EN 60309-2 | 400 V (50+60 Hz) red |
| Clock hour position | 6 h |
| Identification colour | Red |
| Construction type | Flush mounted socket with UP box |
| Configuration | Cover with text label |
| Colour | Grey |
| RAL-number | 7035 |
| Contact material | CuZn |
| Surface finish contacts | Nickel-plated |

| | |
|--------------------|-----------------------|
| wire flexible | 1-2,5 mm ² |
| wire solid | 1-4 mm ² |
| contact screws | 100 Ncm |
| dismantling length | 50 mm |
| stripping length | 10-12 mm |


www.manufacturer-safety.info