


PCE data sheet

| | |
|------------------------|---|
| article# | 8430gv |
| article description | Panel mounted safety socket Design / DIN 49440 IP44 (grey) |
| description long | Panel mounted safety socket Design / DIN 49440 IP44 (grey) housing material: PC/ABS rated current: 16A number of poles: 3 (2P+PE) rated voltage/frequency: 250V~ / 50+60Hz contacts: brass nickel plated connection technology: screwless terminals color: grey (similar to RAL 7035) for installation in cable trunking hinged lid with inscription field (optional: key lock) IP protection class: IP44 |
| GTIN (EAN) | 9003399882456 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.186 kg |
| packaging quantity | 6 |
| minimum order quantity | 6 |

| | |
|-------------------------|---|
| ETIM 7.0 | EC001318 |
| Current supply | Protective contact (SCHUKO) |
| Number of poles | 3 |
| Voltage acc. EN 60309-2 | 230 V (50+60 Hz) blue |
| Identification colour | Blue |
| Construction type | Equipment mounted socket outlet (under plaster) |
| Configuration | Cover with text label |
| Colour | Grey |
| RAL-number | 7035 |
| Contact material | CuZn |
| Surface finish contacts | Nickel-plated |

| | |
|--------------------|-------------------------|
| wire flexible | 1-2x2,5 mm ² |
| wire solid | 1-2x2,5 mm ² |
| dismantling length | 50 mm |
| stripping length | 8-14 mm |



www.manufacturer-safety.info