

---

PRODUCT-DETAILS

# 6131/31-183-500

## 6131/31-183-500 KNX Presence Premium S

---

### Obecné informace

Typ	6131/31-183-500
Id v robku	2CKA006132A0349
EAN	4011395185964
Katalogov popis	6131/31-183-500 KNX Presence Premium S

### Detailn popis

Detection range (for mounting height 2.5 m, 3 m and 4 m): circular. Seated persons : max. 8 m, max. 10 m and max. 14 m. Walking persons : max. 10 m, max. 12 m and max. 16 m. Visible height 23 mm. With 4 channels. For dimming/brightness of the rules to a defined value in a designated collection area. HVAC function for controlling heating and/or cooling systems and ventilation systems in the designated collection area. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light controller with up to two independent channels. Constant light controller with max. 2 outputs for dimming daylight control/rules of two rooflights in the room. Integrated object room temperature controller. 10 freely programmable IR channels (blue and/or white) Incl. 5 logic channels (logic gates, gates, delay and staircase lighting) Evaluation via internal brightness sensor. Weighting of up to 2 external brightness values and the internal brightness sensor possible. The programming button can be activated with the IR transmitter 6010-25 (-500). With integrated KNX bus coupler. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: 68 mm. Suitable for surface mounting installation. Cannot be installed in British Standard or VDE flushmounted box. Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.

---

### Objednací údaje

EAN	4011395185964
slo celn ho sazebn ku	85365080
Minim ln objednac mno stv	1 piece
E-Number (Finland)	2815474
E-Number (Sweden)	1738696

ist hmotnost v robku	81 g
----------------------	------

rove balen 1, jednotky	carton 1 piece
rove balen 1, EAN	4011395185964
rove balen 1, d lka	121 mm
rove balen 1, v ka	62 mm
rove balen 1, ka	96 mm
rove balen 1, hrub hmotnost	0.146 kg

Teplota okoln ho vzduchu	Operation -5 ... +45 C
Compatible Bus Systems	KNX (TP)
Kryt	IP20
Typ upevn n	Surface mounted (plaster)

List s daji, technick informace	2CKA001373B8668
Prohl en o shod - CE	2CKA100000E1060
Pokyny a p ru ky	No document needed
REACH Declaration	2CKA309999E9999
Informace RoHS	2CKA200000E4527

Stav RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-----------	--

ETIM 7	EC001582 - Movement sensor for bus system
ETIM 8	EC001582 - Movement sensor for bus system
Tr da eClass	V11.0 : 27143144

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

---

**Accessories**


---

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006132A0404	6131/38-183-500 Intermediate ring fm box S	6131/38-183-500	1	piece
2CKA006899A2304	6898 Ko ochrann pro stropn p stroje alpine white	6898	1	piece

---



---

**Kategorie**


---

P stroje a rozv d e n z k ho nap t → Home and Building Automation → KNX → Presence Detection → Presence Detectors

