

PRODUCT-DETAILS

432RAU6

432RAU6 Z suvka vestavn íkm , 5p., 32 A,
IP44, 6 h



Obeční informace

| | |
|-----------------|---|
| Typ | 432RAU6 |
| Id v robku | 2CMA193283R1000 |
| EAN | 7392696932837 |
| Katalogov popis | 432RAU6 Z suvka vestavn íkm , 5p., 32 A, IP44, 6 h |
| Detailní popis | Panel mounted socket, earthing sleeve position 6h, rated current 32A, IP44 splashproof, unified flange, angled, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red |

Technické údaje

| | |
|---|-----------------------------------|
| Normy | IEC 60309-1, -2 |
| Funkce | Panel mounted socket |
| Vhodn pro | Socket Outlets for Panel Mounting |
| Vhodn pro v robek třdy | IEC Industrial Plugs and Sockets |
| Jmenovit nap t ² (U _r) | 200/346 é 240/415 V |
| Jmenovit proud (I _n) | 32 A |
| Frekvence (f) | 50 Hz 60 Hz |
| Jmenovit frekvence (f) | 50...60 Hz |
| Mont n ² otvory | 85x85 |
| Počet p ¹ | 5 |
| Plug Angle | Angled |

| | |
|--|------------------------|
| Utahovac ² moment | WireClamp1.2 N m |
| Typ p ípojen ² | Screw |
| Typ upevn ěn ² | Unified angled flange |
| Typ ochrany | Splashproof |
| Clock Position Of Grounding Contact | 6 hour |
| Materi í zapouzd ěn ² | Thermoplastic |
| Materi í pouzdra | Plastic (PA) |
| Materi í | Plastic |
| P řídavn ě informace | 3P+N+E |
| Doporu ěn ě roubov ěk | PH2 |
| RAL Number | RAL 7001 - Silver Grey |
| Barva | Red |
| Pr ěez kabelu/vodí ě | 2.5 ... 10 mm |

daje vn ěj řho prost ěd²

| | |
|--|-----------------------------------|
| Teplota okol ² | -25 ... 40 C |
| Kryt ² | IP44 |
| Stav RoHS | Following EU Directive 2011/65/EU |
| Environment In ² informace | 2CMC000056M0000 |

Technick ě daje UL/CSA

| | |
|--|------------|
| Utahovac ² moment UL/CSA | 10.6 in lb |
|--|------------|

Rozm ěry

| | |
|-------------------------------|-------------|
| ist ě ² ka v robku | 110 mm |
| ist ě v ěka v robku | 110 mm |
| ist ě hloubka v robku | 117 mm |
| ist ě hmotnost v robku | 0.28 kg |
| Velikost | 110X110X117 |

Balen²

| | |
|---|-------------------------|
| rove balen ² 1, jednotky | box 10 piece |
| rove balen ² 1, ěka | 188 mm |
| rove balen ² 1, v ěka | 428 mm |
| rove balen ² 1, d ělka | 175 mm |
| rove balen ² 1, hrub hmotnost | 2.8 kg |
| rove balen ² 1, EAN | 7392696662833 |
| rove balen ² 2, jednotky | pallet (lift) 240 piece |
| rove balen ² 2, ěka | 800 mm |
| rove balen ² 2, v ěka | 900 mm |
| rove balen ² 2, d ělka | 1200 mm |
| rove balen ² 2, hrub hmotnost | 692 kg |
| rove balen ² 2, EAN | 7392696080170 |

Objednac² daje

| | |
|---|---------------------|
| Minim In ² objednac ² mno stv ² | 10 piece |
| Šlo celnho sazebnku | 85366990 |
| E-Number (Finland) | 2421276 |
| E-Number (Norway) | 1547453 |
| E-Number (Sweden) | E2416670 |
| Zem p vodu | Czech Republic (CZ) |

Certifik ty a prohl en² (šla dokument)

| | |
|--|--------------------|
| Prohl en ² | 2CMC700005D0001 |
| Prohl en ² o shod - CE | 2CMC700005D0001 |
| Environment In ² informace | 2CMC000056M0000 |
| Pokyny a p řu ky | No document needed |
| REACH Declaration | 2CMC700005D0001 |
| Informace RoHS | 2CMC700005D0001 |
| Certifik t SEMKO | 1613211 |

Dokumenty ke sta en²

| | |
|------------------------------------|--------------------|
| List s daji, technick informace | 2CMC700006C0201 |
| N vod k instalaci | 2CMC00058M0001 |
| Pokyny a p řu ky | No document needed |
| Mechanick v kresy | 9AKK107991A3780 |

Klasifikace

| | |
|---------------------------------------|--|
| ETIM 7 | EC001317 - Panel-mounted CEE socket outlet |
| ETIM 8 | EC001317 - Panel-mounted CEE socket outlet |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |
| CN8 | 85366990 |
| UNSPSC | 39121406 |
| Trda eClass | 27440504 |
| IDEA Granular Category Code (IGCC) | 4536 >> Electrical receptacles |

Kategorie

P řstroje a rozv d e nžk ho nap t² → Pr myslov vidlice a z svuky → Easy & Safe → Socket Outlets for Panel Mounting

