

KDU 60

Konsolhalter, schwer, 60x40 mm Fluchtweginstallation

Tauchfeuerverzinkt, nach DIN EN ISO 1461


| Artikel | Profilbreite | Profilhöhe | Länge | t | Gewicht |
|------------|--------------|------------|---------|------|---------|
| KDU 60-02F | 60 mm | 40 mm | 200 mm | 6 mm | 1,41 kg |
| KDU 60-03F | 60 mm | 40 mm | 300 mm | 6 mm | 1,77 kg |
| KDU 60-04F | 60 mm | 40 mm | 400 mm | 6 mm | 2,07 kg |
| KDU 60-05F | 60 mm | 40 mm | 500 mm | 6 mm | 2,37 kg |
| KDU 60-06F | 60 mm | 40 mm | 600 mm | 6 mm | 2,72 kg |
| KDU 60-07F | 60 mm | 40 mm | 700 mm | 6 mm | 3,08 kg |
| KDU 60-08F | 60 mm | 40 mm | 800 mm | 6 mm | 3,5 kg |
| KDU 60-09F | 60 mm | 40 mm | 900 mm | 6 mm | 3,82 kg |
| KDU 60-10F | 60 mm | 40 mm | 1000 mm | 6 mm | 4,09 kg |
| KDU 60-11F | 60 mm | 40 mm | 1100 mm | 8 mm | 4,9 kg |
| KDU 60-12F | 60 mm | 40 mm | 1200 mm | 8 mm | 5,2 kg |
| KDU 60-13F | 60 mm | 40 mm | 1300 mm | 8 mm | 5,5 kg |
| KDU 60-14F | 60 mm | 40 mm | 1400 mm | 8 mm | 5,9 kg |
| KDU 60-15F | 60 mm | 40 mm | 1500 mm | 8 mm | 6,3 kg |
| KDU 60-16F | 60 mm | 40 mm | 1600 mm | 8 mm | 6,6 kg |
| KDU 60-17F | 60 mm | 40 mm | 1700 mm | 8 mm | 7 kg |
| KDU 60-18F | 60 mm | 40 mm | 1800 mm | 8 mm | 7,3 kg |
| KDU 60-19F | 60 mm | 40 mm | 1900 mm | 8 mm | 7,7 kg |
| KDU 60-20F | 60 mm | 40 mm | 2000 mm | 8 mm | 7,8 kg |



t: Materialstärke

Gewicht: Gewicht je Lagereinheit

DETAIL- UND ANWENDUNGSBILDER



| B | L _k | F _b /P |
|-----|----------------|-------------------|
| mm | mm | |
| 100 | 120 | 1,2 |
| 200 | 220 | 1,5 |
| 300 | 320 | 1,9 |
| 400 | 420 | 2,2 |

