

## EB-MFD044S6 586306

Objednáací kód: EB-MFD044S6 586306

Materiál: **Nerezová ocel**  
Povrch: **Ostatní**  
Nominal inner diameter: **DN32**  
Inlay: **Pryž**  
Přípustná užitiná zátěž: **1000**  
Connection size, connection facility: **M8/M10**  
Suitable for number of pipes: **1**  
KIWA certified: **Ne**  
FM quality mark: **Ne**  
UL quality mark: **Ne**  
LPCB quality mark: **Ne**  
Suitable for stainless steel tube: **Ano**  
Suitable for aluminium tube: **Ano**  
Suitable for plastic tube: **Ano**  
Max. medium temperature (continuous): **110**

Jakost materiálu: **Ušlechtilá ocel 316 (1.4401)**  
Surface treatment: **Polished**  
Outer pipe diameter: **37**  
Inlay damping value:  
Connection facility: **Vnitřní závit**  
Lock facility: **Double screw**  
Šířka: **20**  
Permitted by NCP: **Ne**  
VdS quality mark: **Ne**  
ULC quality mark: **Ne**  
Suitable for steel tube: **Ano**  
Suitable for copper tube: **Ano**  
Vhodné pro litinové trubky: **Ano**  
Suitable for pipe coil: **Ano**  
Min. medium temperature (continuous): **-50**



---

### Příslušenství