

EB-MFD050S6 586307

Objednací kód: EB-MFD050S6 586307

Materiál: **Nerezová ocel**
Povrch: **Ostatní**
Nominal inner diameter: **DN 40**
Inlay: **Pryž**
Přípustná užitná zátěž: **1300**
Connection size, connection facility: **M8/M10**
Suitable for number of pipes: **1**
KIWA certified: **Ne**
FM quality mark: **Ne**
UL quality mark: **Ne**
LPCB quality mark: **Ne**
Suitable for stainless steel tube: **Ano**
Suitable for aluminium tube: **Ano**
Suitable for plastic tube: **Ano**
Max. medium temperature (continuous): **110**

Jakost materiálu: **Ušlechtilá ocel 316 (1.4401)**
Surface treatment: **Polished**
Outer pipe diameter: **44**
Inlay damping value:
Connection facility: **Vnitřní závit**
Lock facility: **Double screw**
Šířka: **20**
Permitted by NCP: **Ne**
VdS quality mark: **Ne**
ULC quality mark: **Ne**
Suitable for steel tube: **Ano**
Suitable for copper tube: **Ano**
Vhodné pro litinové trubky: **Ano**
Suitable for pipe coil: **Ano**
Min. medium temperature (continuous): **-50**



Příslušenství