

# Splashproof garden post with single socket outlet, side earthing and spike, white

701-36815

4 year warranty

The garden post includes one socket outlet (16 A/250 Vac) with side earthing, shutters and plug-in terminals. It has an IP55 protection degree and is equipped with a spike that needs to be driven directly into the earth. Its functional and beautiful design makes the garden post a perfect fit for outdoor areas, such as on terraces and in outdoor kitchens. Moreover, the entire unit is splashproof, which makes it extremely well-suited for use in damp areas and demanding environments.

Wires that remain fixed:

- wire is fixed firmly due to the high-quality plug-in terminal with a long life span, tested according to the norm
- since the conductor release on the mechanisms is located at the front, the wiring cannot push on the release when you place it in the box

Faster and easier installation:

- all connections terminals are located at the top of the base:
  - to ensure all wires can be cut and stripped at the same length
  - to guarantee more space under the mechanism, so you can easily fold the wires and place the mechanism in the box without the wiring pushing it back up.

Niko quality:


- long life span since the plug-in terminal stays within the limits of the norm during a temperature and power drop

## Technical data

Splashproof garden post with single socket outlet, side earthing and spike, white. Handmade product: small deviations in form may occur

- Function: – wall socket outlet
  - contact buses with a large contact surface that do not rest on the base in order to be connected
- Maximum MCB rating: 16 A (1.5 mm<sup>2</sup>) / 20 A (2.5 mm<sup>2</sup>) (limited by national installation rules)
- Number of mechanisms: 1
- Chemical resistance: ammonia-rich environments may cause faster ageing of the base
- Protection degree: IP55 for the combination of a socket outlet and a splashproof mounting box
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: white (coloured in mass, approximately NCS S 0502 - Y50R, RAL 9010)
- Dimensions (HxWxD): 240 x 83 x 68 mm
- Certification marks: KEMA, ÖVE, SEMKO
- Marking: CE
- Material housing: stainless steel




 16 A  
250 Vac



**niko**

701-36815 - 29-02-2024

## Dimensions



## Wiring diagram

