

PŘÍVODKY VESTAVNÉ - ÚHEL 90°

Amp	Póly	Obrázek	230 V- 50/60 Hz	400 V- 50/60 Hz	Hodinový úhel	Laněný vodič (mm ²)	Hmotnost ks	Balení
16	3		13250	-	6h	1 - 2,5	127	4
	4		-	13350	6h	1 - 2,5	147	4
	5		-	13351	6h	1 - 2,5	167	4
32	3		13253	-	6h	2,5 - 6	230	2
	4		-	13352	6h	2,5 - 6	250	2
	5		-	13353	6h	2,5 - 6	273	2



ZÁSUVKY VESTAVNÉ - ÚHEL 90°

Amp	Póly	Obrázek	230 V- 50/60 Hz	400 V- 50/60 Hz	Hodinový úhel	Laněný vodič (mm ²)	Hmotnost ks	Balení
16	3		23250	-	6h	1 - 2,5	172	4
	4		-	23350	6h	1 - 2,5	182	4
	5		-	23351	6h	1 - 2,5	241	2
32	3		23253	-	6h	2,5 - 6	290	2
	4		-	23352	6h	2,5 - 6	296	2
	5		-	23353	6h	2,5 - 6	332	2



16	3		14250	-	6h	1 - 2,5	167	4
	4		-	14350	6h	1 - 2,5	187	4
	5		-	14351	6h	1 - 2,5	207	4
32	3		14253	-	6h	2,5 - 6	265	2
	4		-	14352	6h	2,5 - 6	285	2
	5		-	14353	6h	2,5 - 6	307	2



16	3		24250	-	6h	1 - 2,5	135	4
	4		-	24350	6h	1 - 2,5	215	4
	5		-	24351	6h	1 - 2,5	241	2
32	3		24253	-	6h	2,5 - 6	290	2
	4		-	24352	6h	2,5 - 6	296	2
	5		-	24353	6h	2,5 - 6	332	2



PŘÍVODKY VESTAVNÉ - PŘÍMÉ

16	4		-	13370	6h	1 - 2,5	109	10
	5		-	13371	6h	1 - 2,5	124	8
32	4		-	13372	6h	2,5 - 6	151	5
	5		-	13373	6h	2,5 - 6	174	5



ZÁSUVKY VESTAVNÉ - PŘÍMÉ

16	3		23270	-	6h	1 - 2,5	138	10
	3		23480	-	6h	1 - 2,5	138	10
	4		-	23370	6h	1 - 2,5	152	10
	5		-	23371	6h	1 - 2,5	175	8
	3		23273	-	6h	2,5 - 6	203	5
32	4		-	23372	6h	2,5 - 6	210	5
	5		-	23373	6h	2,5 - 6	245	5

