

SEO motor operator 42–60 V AC/DC accessory for: 3VA2
100/160/250



Model	
Product brand name	SETRON
Product designation	Accessories
Product version	Motorized operating mechanism with stored energy mechanism (SEO)





Voltage	
Type de tension pour la commande	AC/DC
<ul style="list-style-type: none"> Rated control supply voltage U_s at AC 50 Hz 	42 V
<ul style="list-style-type: none"> Rated control supply voltage U_s at AC 50 Hz 	60 V
<ul style="list-style-type: none"> Rated control supply voltage U_s at AC 60 Hz 	42 V
<ul style="list-style-type: none"> Rated control supply voltage U_s at AC 60 Hz 	60 V
Rated operational power	300 V·A

Mechanical Design	
Rated control supply voltage U_s with DC	42 V
Height	118.7 mm
Width	104.6 mm
Depth	162.8 mm
Connectable conductor cross-section / solid	

<ul style="list-style-type: none"> • minimum • maximum 	<p>1.5 mm²</p> <p>2.5 mm²</p>
Connectable conductor cross-section / finely stranded / with core end processing <ul style="list-style-type: none"> • minimum • maximum 	<p>1.5 mm²</p> <p>2.5 mm²</p>
Connectable conductor cross-section / stranded <ul style="list-style-type: none"> • minimum • maximum 	<p>1.5 mm²</p> <p>2.5 mm²</p>
Ambient temperature / during operation <ul style="list-style-type: none"> • minimum • maximum 	<p>-25 °C</p> <p>70 °C</p>
Ambient temperature / during storage <hr/>	<p>-40 ... +80</p>
Tightening torque <ul style="list-style-type: none"> • minimum • maximum 	<p>0.36 N·m</p> <p>0.44 N·m</p>

Connections according IEC	
Wire stripping length	7 mm



Certificates

General Product Approval	EMC	Declaration of Conformity	Shipping Approval	other
Miscellaneous 				Manufacturer Declaration
	RCM	EG-Konf.	LRS	

other
Miscellaneous

Further information

- Information- and Downloadcenter (Catalogs, Brochures,...)**
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)**
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9267-0HC20>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
<https://support.industry.siemens.com/cs/ww/en/ps/3VA9267-0HC20>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9267-0HC20
- CAX-Online-Generator**
<http://www.siemens.com/cax>



last modified:

08/08/2020