


**DG SE DC 60 FM (972 115)**


- Universal single-pole surge arrester consisting of a base part and a plug-in protection module
- Powerful d.c. switching device DCD
- Can be used without additional backup fuse



Figure without obligation



Basic circuit diagram DG SE DC 60 FM



Dimension drawing DG SE DC 60 FM

Modular single-pole surge arrester for d.c. applications; with floating remote signalling contact.

Type Part No.	DG SE DC 60 FM 972 115
SPD according to EN 61643-11 / IEC 61643-11	type 2 / class II
Energy coordination with terminal equipment (≤ 10 m)	type 2 + type 3
Nominal voltage (d.c.) (U <sub>N</sub> )	48 V
Max. continuous operating voltage (d.c.) (U <sub>C</sub> )	60 V
Nominal discharge current (8/20 μs) (I <sub>n</sub> )	12.5 kA
Voltage protection level (U <sub>P</sub> )	≤ 0.5 kV
Response time (t <sub>A</sub> )	≤ 25 ns
Short-circuit withstand capability without backup fuse (d.c.) (I <sub>SCCR</sub> )	300 A
Short-circuit withstand capability for max. mains-side overcurrent protection (d.c.) (I <sub>SCCR</sub> )	25 kA
Max. mains-side overcurrent protection	35 A gG
Temporary overvoltage (TOV) d.c. (U <sub>T</sub> ) - Characteristic	70 V / 5 sec. – withstand
Temporary overvoltage (TOV) d.c., 2x U <sub>C</sub> (U <sub>T</sub> ) - Characteristic	120 V / 120 min. – safe failure
Operating temperature range (T <sub>U</sub> )	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm <sup>2</sup> solid / flexible
Cross-sectional area (max.)	35 mm <sup>2</sup> stranded / 25 mm <sup>2</sup> flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP20
Capacity	1.5 module(s), DIN 43880
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm <sup>2</sup> solid / flexible
Extended technical data:	use for safety lighting systems
- d.c. and a.c. operation	no
Weight	142 g
Customs tariff number (Comb. Nomenclature EU)	85363030
GTIN	4013364158511
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.