


BCO MOD ML2 BD EX 24 (927 084)


- LifeCheck arrester monitoring and integrated status indication
- Two-pole arrester module for optimal protection of one pair in intrinsically safe signal circuits
- For installation in conformity with the lightning protection zone concept at the boundaries from $O_A - 2$ and higher



Figure without obligation



Basic circuit diagram BCO MOD ML2 EX 24



Dimension drawing BCO MOD ML2 EX 24

Protection module with a width of 6 mm for BLITZDUCTORconnect combined arresters with status indication for protecting one pair of intrinsically safe measuring circuits and bus systems, meets FISCO requirements. Insulation strength > 500 V line-ground.

Type	BCO MOD ML2 BD EX 24
Part No.	927 084
SPD class	TYPE 1 P2
Impulse category	D1, C1, C2, C3, B2
Nominal voltage (U_N)	24 V
Max. continuous operating voltage (d.c.) (U_C)	36 V
Max. continuous operating voltage (a.c.) (U_C)	25.4 V
Nominal current at 80 °C (I_N)	0.5 A
D1 Total lightning impulse current (10/350 μ s) (I_{imp})	3 kA
D1 Lightning impulse current (10/350 μ s) per line (I_{imp})	1.5 kA
C2 Total nominal discharge current (8/20 μ s) (I_n)	10 kA
C2 Nominal discharge current (8/20 μ s) per line (I_n)	5 kA
Voltage protection level line-line for I_n C2 (U_p)	≤ 65 V
Voltage protection level line-PG for I_n C2 (U_p)	≤ 1100 V
Voltage protection level line-line for I_n C1 (U_p)	≤ 65 V
Voltage protection level line-PG for I_n C1 (U_p)	≤ 1100 V
Voltage protection level line-line at 1 kV/ μ s C3 (U_p)	≤ 48 V
Voltage protection level line-PG at 1 kV/ μ s C3 (U_p)	≤ 1000 V
Series resistance per line	1 ohm(s)
Cut-off frequency line-line (f_c)	3.5 MHz
Capacitance line-line (C)	≤ 2 nF
Capacitance line-PG (C)	≤ 15 pF
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Degree of protection (with plugged-in protection module)	IP 20
Plugs into	BCO Ex base part
Earthing via	BCO Ex base part
Enclosure material	polyamide PA 6.6
Colour	blue
Test standards	IEC 61643-21 / EN 61643-21
Approvals	EAC, ATEX, IECEX, CCC, SIL
ATEX approvals (1)	TÜV 19 ATEX 8476 X: II (1)2 G Ex ia [ia Ga] IIC T4 ... T6 Gb
ATEX approvals (2)	TÜV 19 ATEX 8476 X: II 2 G Ex ib IIC T4 ... T6 Gb
ATEX approvals (3)	TÜV 19 ATEX 8476 X: II (1) D [Ex ia Da] IIIC
IECEX approvals (1)	IECEX TUR 20.0025X: Ex ia [ia Ga] IIC T4 ... T6 Gb
IECEX approvals (2)	IECEX TUR 20.0025X: Ex ib IIC T4 ... T6 Gb
IECEX approvals (3)	IECEX TUR 20.0025X: [Ex ia Da] IIIC
China Compulsory Certification	CCC No. 2021312304001130 (Ex ia, Ex ib)
Extended technical data:	-----
- Max. discharge current (8/20 μ s) [1/2 - PG], [1+2 - PG] (I_{max})	20 kA
- Discharge current (8/20 μ s) [1/2 - PG], [1+2 - PG]	10 kA (10x)
- Voltage protection level line-PG at 1 kV/ μ s C3 after being subjected to I_{max} (U_p)	≤ 1000 V
Weight	14 g
Customs tariff number (Comb. Nomenclature EU)	85363010
GTIN	4013364410206

Product Data Sheet: BLITZDUCTORconnect – Modular



Type	BCO MOD ML2 BD EX 24
Part No.	927 084
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.