

## End and transition grommets, wall and ceiling elbows 30°



### Wall and ceiling elbow 30°

- for connecting conduits or as a ceiling outlet
- with sealing membrane at the formwork interface
- suitable for all types of formwork

<b>Order number:</b>	<b>1202-29</b>
EAN:	4013456350212
Length	80 mm
Width	41 mm
Height	83 mm
DIN EN conduit Ø	32 mm
Number of parts	2
Visible area Ø	35 mm
Packaging inner/dispatch	25/100

End and transition grommets, and wall and ceiling 30°-elbows, for ensuring a continuously functioning conduit system at transition points. The particularly compact design of the end and transition grommets enables conduit outlets to be easily arranged - even between closely spaced reinforcement bars without needing to adjust the bars. The optimum elbow radius of the wall and ceiling elbow fittings, and their precisely fitting conduit entries, avoid the occurrence of protruding edges at interfaces, thus ensuring that cables can be freely inserted from both ends.

- Compact design for easy installation between closely spaced reinforcement bars
- Optimal elbow radius for easy cable insertion
- Installation against the (as yet unplaced) front formwork by means of a support strut with base plate to the rear formwork
- Two-part design with secure snap-in connection
- Easy removal of the sealing membrane
- Small visible area for neat wall/ceiling appearance

