

## Prefix® concrete building box for attaching to the reinforcement



### Prefix® concrete building box 60

- One-gang junction box for fixing to the reinforcement
- One-piece with moulded-on front part
- With 4 screw domes and 2 expanding claw fields on each opening side
- combinations have fully-insulated cable transitions
- Standardised combination distance 71 mm

<b>Order number:</b>	<b>1211-61</b>
EAN:	4013456545649
Width	290 mm
Depth	95 mm
Installation opening Ø	60 mm
for concrete covers	20-60 mm
Markings for cables and DIN EN conduits up to Ø 25 mm	6
Packaging inner/dispatch	25/50

Concrete building boxes with Prefix® installation technology and two integrated front parts ensure an additional improvement during fitting to the formwork. The Prefix concrete building boxes can be pre-fitted using spring-loaded installation clamps. A peripheral, pronounced corrugated profile along the installation clamps for use with tie wires prevents slipping during fixing. If extreme loads are expected, additional opportunities for attaching tie wires exist along the mounting profile. Together with a more compact form, this simplifies working, which ensures exact positioning of the box and a clean wall appearance.

- Fast, easy installation on rebar without support element before front formwork placed against it
- Holding in place using the Prefix® installation technology leaves both hands free for securing with tying wire
- A pronounced corrugated profile and additional fixing opportunities for secure fixing using tie wires
- Suitable for 20 - 60 mm concrete covers
- For facing concrete installation to the opposing formwork
- Can be combined to create standardised stable multiple combinations

