

Air-tight cavity wall installation



LUFTDICHT



O-range ECON® 64 one-gang junction box

- Air-tight design with sealing membranes
- Fully insulated, air-tight through-wiring for combinations using support connectors
- Toolless cable or conduit entries
- Integrated cable retention of NYM cables, self-locking of conduits

Order number: 9264-78

EAN: 4013456548305

For panel thickness 7 - 40 mm

Depth 62 mm

Cut hole Ø 68 mm

Device screws 2

Tube entries up to M25 2

Cable entries 5 x 2.5 mm² or 7 x 1.5 mm² 1

Cable entries 3 x 2.5 mm² or 5 x 1.5 mm² 3

Cable entries 3 x 1.5 mm² 3

Support connectors for each package 7

Air-tight Yes

Halogen-free Yes

Packaging inner/dispatch 25/250

Air-tight O-range® cavity wall boxes with ECON® technology for energy-efficient electrical installation according to EnEV and for installations under clean-room and hygiene conditions. The elastic ECON® technology sealing membrane allows air-tight electrical installation.

- Elastic sealing membrane for guaranteed air-tightness
- Innovative clamp technology with integrated cable retention
- Tool-free cable and conduit entry
- Air-tight combined with support connector

O-range ECON®     