


RAPIDv2 LED

Světelný zdroj LED



RAPID v2 E27

RAPID v2 E27-NW	22944	4,9	41	500	4000	180	E27	F
RAPID v2 E27-WW	22945	4,9	41	500	3000	180	E27	F
RAPID PRO v2 E27-NW	22946	8	60	810	4000	180	E27	F
RAPID PRO v2 E27-WW	22947	8	60	810	3000	180	E27	F
RAPID MAXX v2 E27-NW	22948	9,5	74	1050	4000	180	E27	E
RAPID MAXX v2 E27-WW	22949	9,5	74	1050	3000	180	E27	E
RAPID HI v2 E27-NW	22954	13	99	1520	4000	180	E27	E
RAPID HI v2 E27-WW	22955	13	99	1520	3000	180	E27	E

Zdroje Kanlux RAPIDv2 E27 byly vyrobeny s maximální pozorností na každý detail. Vyznačují se především vysokým světelným tokem a světelnou účinností dosahující téměř 117 lm/W (RAPID HI). Další výhodou těchto zdrojů je hybridní konstrukce pláště.

- Materiál: plast
- Materiál difuzoru: plast

RAPIDv2 LED

Světelný zdroj LED



RAPID v2 E27




RAPID PRO v2 E27




RAPID MAXX v2 E27




RAPID HI v2 E27



RAPID v2 E27; RAPID PRO v2 E27



RAPID MAXX v2 E27



RAPID HI v2 E27