


SR D50 4700 FSP1000 IP HVI GFK V2A (105 316)



Figure without obligation



Supporting tube with internal sealing end and EB spring element. Air-termination tip Ø10 mm.

Type	SR D50 4700 FSP1000 IP HVI GFK V2A
Part No.	105 316
Material of air-termination tip	StSt
Length of air-termination tip	1000 mm
Material of supporting tube	GRP / StSt
Length of supporting tube	4700 mm
Transport length	4700 mm
Outside diameter Ø	50 mm
Length of insulating clearance	1535 mm
Wall thickness	3 mm
Material factor km	0.7
Permanent temperature range	-50 °C ... +100 °C
Type	UV-stabilised
Sleeve	60 x 5 mm
Max. free length with air-termination tip (wall mounting)	3500 mm
Max. gust wind speed (wall mounting, 1x HVI inside)	234 km/h
Max. gust wind speed (wall mounting, 1x HVI outside)	229 km/h
Max. gust wind speed (wall mounting, 4x HVI outside)	200 km/h
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	15,6 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364157798
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.