

SR D50 3500 FS2500 IA HVIP GFK AL (105 573)



Figure without obligation



Supporting tube with internal sealing end and EB spring element. Air-termination rod $\varnothing 22 / 16 / 10$ mm.

Type	SR D50 3500 FS2500 IA HVIP GFK AL
Part No.	105 573
Material of air-termination rod	Al
Length of air-termination rod	2500 mm
Material of supporting tube	GRP / Al
Length of supporting tube	3500 mm
Outside diameter \varnothing	50 mm
Transport length	3500 mm
Wall thickness	4 mm
Material factor km	0.7
Length of insulating clearance	1800 mm
Permanent temperature range	-50 °C ... +100 °C
Type	UV-stabilised
Sleeve	60 x 5 mm
Suitable for installation outside the tube	yes
Max. free length with air-termination rod (wall mounting)	5500 mm
Max. gust wind speed (wall mounting, 1x HVI power inside)	173 km/h
Max. gust wind speed (wall mounting, 1x HVI power inside + 1x HVI power outside)	155 km/h
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	6,4 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364271975
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.