

EKS TI KVS SBK (766 302)

- Partly insulated (TI), shock-proof version
- Fully equipped kit for cable distribution cabinets
- Other cable lengths can be selected online via the earthing and short-circuiting configurator



Figure without obligation

Figure without obligation

Kit includes:

| Pos. | Part No. | Pos. | Part No. |
|------|------------|------|------------|
| 1 | 1x 766 300 | 6 | 3x 745 018 |
| 3 | 1x VSUN6NV | 9 | 1x 745 400 |

For more detailed information on these products, see Accessories chapter.

| Type | EKS TI KVS SBK |
|---|---------------------------------|
| Part No. | 766 302 |
| Variant No. of EaS device | VSUN6NV |
| Dimensions | 380 x 260 x 80 mm |
| Standard | EN/IEC 61230 (DIN VDE 0683-100) |
| Temperature range | -25 °C ... +55 °C |
| Weight | 4,38 kg |
| Customs tariff number (Comb. Nomenclature EU) | 85369095 |
| GTIN | 4013364051317 |
| PU | 1 pc(s) |

Attention: Please state the relevant Variant No. when ordering.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.