

## UK K25 FL30 SQL (773 251)

- Universal clamp, T pin shaft
- T pin according to DIN 48087
- For flat and round conductors up to 30 mm and fixed ball points, ball Ø25 mm



Figure without obligation




Figure without obligation

*) Klemmbereich und Seilquerschnitt für Uniklemmen an:			
Kugelfestpunkt Ø	T-Anschluss Halsweite	Rd / Fl Klemmbereich	Seilquerschnitt
20/25/30 mm	15/18 mm	20/30 mm	16 mm <sup>2</sup>
20/25/30 mm	15/18 mm	20/30 mm	25 mm <sup>2</sup>
20/25/30 mm	15/18 mm	20/30 mm	35 mm <sup>2</sup>
20/25/30 mm	15/18 mm	20/30 mm	50 mm <sup>2</sup>
20/25/30 mm	15/18 mm	20/30 mm	70 mm <sup>2</sup>
20/25/30 mm	15/18 mm	-	95 mm <sup>2</sup>
-/25/30 mm	-	-	120 mm <sup>2</sup>
-	-	-	150 mm <sup>2</sup>

Type	UK K25 FL30 SQL
<b>Part No.</b>	<b>773 251</b>
For fixed ball point Ø	25 / 30 mm
Anti-rotation cable lug	PK2 (Ø10.5 mm)
For cable cross section Cu	50 mm <sup>2</sup>
Max. short-circuit current I <sub>k</sub> 0.06 s	34.0 kA
DB drawing No.	4 Ebgw 01.59
DB material No.	157 538
Material (pressure plate)	St/gal Zn
Material (clamp body)	Copper alloy
Material (shaft)	Stainless steel
Weight	901 g
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364005990
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.