



## RD 10 STTZN R30M (800 310)



Figure without obligation

Steel wire according to EN 62561-2 with zinc coating  $\geq 50 \mu\text{m}$  on average (about  $350 \text{ g/m}^2$ ), for use in lightning protection and earth-termination systems.

Type	RD 10 STTZN R30M
Part No.	800 310 ✓
Diameter $\varnothing$ conductor	10 mm
Cross-section	$78 \text{ mm}^2$
Material	St/tZn
Standard	based on EN 62561-2
Zinc sheath	$\geq 50 \mu\text{m}$ average (about $350 \text{ g/m}^2$ )
Conductivity	$\geq 6.66 \text{ m} / \text{Ohm mm}^2$
Resistivity	$\leq 0.25 \text{ Ohm mm}^2 / \text{m}$
Short-circuit current (AC 50 Hz / DC) (1 s; $\leq 300 \text{ }^\circ\text{C}$ )	5.5 kA
Weight	617 g/m
Customs tariff number (Comb. Nomenclature EU)	72172030
GTIN	4013364131064
PU	30 m

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Conductor materials can only be supplied in the original coil weights.

Further conductor materials as specified in the standard series EN 62561-2 are available on request.