

## EKV3+1 70 R VQYP8B2 (VQYP8B2)

Bestelldaten	Typ	Beschreibung
Variantennummer <b>VQYP8B2</b>	EKV3+1 70 R	3-polige Erdungs- und KurzschlieÙvorrichtung nach DIN VDE 0683 Teil 100 (EN/IEC 61230) Selbstanschnitt: 70 mm² / 35 mm² Maximaler Kurzschlussstrom / -dauer: 19,5 kA / 0,5 s - 2,5
		Länge A: 600 mm Länge B: 600 mm Länge C: 600 mm Länge D: 1800 mm
	KKH 20 SK	Kugelschraubstecker Ø20 mm, Spindel mit Sechskant Art.-Nr. 772 310 Datenblatt Art.-Nr. 772 310 (Typ KKH 20 SK)
	EAS EK FM 12	Erdanschliesstück M12, mit Fingelschraube Art.-Nr. 775 621 Datenblatt Art.-Nr. 775 621 (Typ EAS EK FM 12)




Figure without obligation

Type	EKV3+1 70 R VQYP8B2
<b>Part No.</b>	<b>VQYP8B2</b>
Phase cable end	KKH 20 SK
Earth cable end	EAS EK FM 12
For fixed ball point Ø	20 mm
Cable cross-section Cu	70/35 mm <sup>2</sup>
Max. short-circuit current I <sub>k</sub> 0.5 s	19.5 kA
Max. short-circuit current I <sub>k</sub> 1 s	13.8 kA
Standard	EN/IEC 61138 (DIN VDE 0283-3) and EN/IEC 61230 (DIN VDE 0683-100)
Temperature range	-25 °C ... +55 °C
Material (cable)	E-Cu, extra finely stranded and highly flexible
Material (sheath)	Thermoplastic (soft PVC compound YM2)
Weight	7,15 kg
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364163195
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.