


# ZETA M, B



<b>Name</b>	ZETA M, B
<b>Code</b>	2250633D
<b>Color</b>	BLACK / RAL 9005
<b>Power</b>	25W ± 10 %
<b>Lumen output</b>	2500lm ± 10 %
<b>Color temperature</b>	3000K
<b>Efficacy</b>	100lm/W
<b>Driver</b>	600 mA
<b>Electrical insulation class</b>	Ⅲ
<b>Voltage / Frequency</b>	220-240V/50-60Hz
<b>Color Rendering Index</b>	90+
<b>SDCM</b>	< 3
<b>Light beam angle</b>	90°
<b>Unified Glare Rating</b>	<19
<b>Light source</b>	LED
<b>Dimmable</b>	DALI/PUSH
<b>LED Lifetime</b>	L80B20 50.000h 25°C
<b>Warranty</b>	5 YEAR
<b>Ingress Protection</b>	IP 44
<b>Material</b>	ALUMINIUM/PMMA

## Product

Name  
ZETA M, B  
Code  
2250633D  
Color  
BLACK / RAL 9005

## Power

25W ± 10 %  
2500lm ± 10 %  
3000K  
100lm/W  
600 mA



220-240V/50-60Hz

## Information

90+  
< 3  
90°  
<19  
LED  
DALI/PUSH  
L80B20 50.000h 25°C  
5 YEAR

## Other data

IP 44  
ALUMINIUM/PMMA

## EN

Recessed round light fitting for interior mounting with low height, equipped with SMD LEDs. Diffused lighting. Housing made of aluminium, prismatic opal diffuser with low glare index. Available in 4 sizes, white or black color.

Application:

general lighting, intended for residential or commercial areas (hallway, offices, entrance areas, general room lighting, working areas)

## CZ

Kruhové zapuštěné svítidlo určeno pro montáž do interiéru s nízkou montážní výškou. Světelný zdroj - LED SMD. Svítidlo je vyrobeno z hliníku, prizmatický difuzor s nízkým indexem oslnění. Rozptýlené světlo. K dispozici ve 4 velikostech, bílé nebo černé.

Použití:

všeobecné osvětlení obytných nebo komerčních prostor (hala, kancelář, vstupní prostor, všeobecné osvětlení místnosti)

## DE

Runde Einbauleuchte für die Innenmontage mit geringer Bauhöhe, ausgestattet mit SMD-LEDs. Gehäuse aus Aluminium, prismatischer Opal-Diffusor mit niedrigem Blendungsindex. Diffuses Licht. Erhältlich in 4 Größen, weiß oder schwarz.

Anwendung:

Allgemeinbeleuchtung für Wohn- oder Geschäftsräume (Flur, Büro, Eingangsbereich, allgemeine Raumbeleuchtung)

## SK

Kruhové zapuštěné svietidlo určené pre montáž do interiéru s nízkou montážnou výškou. Svetelný zdroj - LED SMD. Svietidlo je vyrobené z hliníka, prizmatický difúzor s nízkym indexom oslnenia. Rozptýlené svetlo. K dispozícii v 4 veľkostiach, biele alebo čierne.

Použitie:

všeobecné osvetlenie obytných alebo komerčných priestorov (hala, kancelária, vstupný priestor, pracovné miesta, izby)