


YOYO 65, B



Name	YOYO 65, B
Code	6233753
Color	BLACK / RAL 9005
Power	16W ± 10 %
Lumen output	1760lm ± 10 %
Color temperature	3000K/3500K/4000K
Efficacy	110lm/W
Driver	fixed / not changeable
Electrical insulation class	
Voltage / Frequency	220-240V/50-60Hz
Color Rendering Index	90+
SDCM	< 3
Light beam angle	110°
Unified Glare Rating	N/A
Light source	LED
Dimmable	ON/OFF
LED Lifetime	L80B20 35.000h 25°C
Warranty	5 YEAR
Ingress Protection	IP 20
Material	ALUMINIUM/PC

Product

YOYO 65, B
6233753
BLACK / RAL 9005

Power

16W ± 10 %
1760lm ± 10 %
3000K/3500K/4000K
110lm/W
fixed / not changeable



220-240V/50-60Hz

Information

90+
< 3
110°
N/A
LED
ON/OFF
L80B20 35.000h 25°C
5 YEAR

Other data

IP 20
ALUMINIUM/PC

EN

Compact diffused luminaire designed for mounting in 3-circuit rails. Available in 2 sizes, white and black. Use: thanks to the variability of the luminaire, it is especially suitable for diffuse lighting of spaces (shops, libraries, galleries, shops)

DE

Kompakte diffuse Leuchte für die Montage in 3-Phasen-Schienen. Erhältlich in 2 Größen, weiß und schwarz. Verwendung: dank der Variabilität der Leuchte besonders geeignet für die diffuse Beleuchtung von Räumen (Geschäfte, Bibliotheken, Galerien, Shops)

CZ

Kompaktní difúzní svítidlo určené pro montáž do 3-okruhových lišt. Dostupné ve 2 velikostech, v bílé a černé barvě. Použití: díky variabilitě svítidla je vhodné zejména na difúzní osvětlení prostor (obchody, knihovny, galerie, prodejny)

SK

Kompaktné difúzne svietidlo určené pre montáž do 3-okruhových lišt. Dostupné v 2 veľkostiach, v bielej a čiernej farbe. Použitie: vďaka variabilite svietidla je vhodné najmä na difúzne osvetlenie priestorov (obchody, knižnice, galérie, predajne)

